

Prostate Central Gland Segmentation Using a Spherical Template Driven Graph Approach

Jan Egger, Ph.D., Ph.D.^{1,2,3}, Tobias Penzkofer, M.D.^{1,4}, Tina Kapur, Ph.D.¹, Clare Tempany, M.D.¹

¹ Dept. of Radiology, Surgical Planning Lab, Brigham and Women's Hospital Boston, MA, USA

² Dept. of Mathematics and Computer Science, University of Marburg, Marburg, Germany

³ Dept. of Neurosurgery, University of Marburg, Marburg, Germany

⁴ Dept. of Diagnostic and Interventional Radiology, RWTH Aachen University Hospital, Germany

Purpose

Prostate cancer is the most abundant cancer in men, with over 240,000 expected new cases and around 28,000 deaths in 2012 in the US alone [1]. Accurate risk stratification for each individual cancer is central to a successful treatment strategy, especially because of the high incidence rate of less aggressive prostate cancers, and the high complication rate of radical prostatectomy. Diagnostic prostate magnetic resonance imaging (MRI) and MRI guided prostate biopsies have demonstrated improved diagnostic discrimination rates of the different types of cancer [2]. Our goal is to enhance the state of the art in automated segmentation (i.e. delineation) of organ limits for the prostate, a step that has been shown to facilitate efficient MR-guided biopsy.

Methods

The Nugget-Cut scheme [3] was used for prostate center gland segmentation on 5 datasets [4]. It sets up a directed 3D-graph $G(V,E)$ in two steps: (I) sending rays through the surface points of a polyhedron and (II) sampling the graph's nodes $n \in V$ along every ray (Figure 1). Additionally, a corresponding set of edges $e \in E$ is generated, which consists of edges between the nodes and edges that connect the nodes to a source s and a sink t . After graph construction – the center of the polyhedron was defined by the user and located inside the prostate center gland – the minimal cost closed set on the graph is computed via a polynomial time s - t -cut [5], which results in the segmentation of the prostate center gland's boundaries and volume. A C++ module was implemented within the medical prototyping platform MeVisLab (see <http://www.mevislab.de>) for evaluation. Results were compared to an expert segmentation using the Dice Similarity Coefficient (DSC).




Fig 1. Nugget-Cut Scheme: A template is used as a basic structure for the segmentation graph

Results

A DSC of $85 \pm 6.0\%$ overlap was achieved compared to expert segmentation. This is an improvement on recent 80% DSC reported in the literature [6]. In our C++ implementation the overall segmentation: (1) sending rays, (2) graph construction and (3) mincut computation, took about one second on an Intel Core i7 CPU, 4x2.50 GHz, 8 GB RAM. Figure 2 shows the segmentation result of a prostate central gland (red) on an axial and a sagittal 2D slice with the typical user-defined seed point position on the axial slice (blue arrow) located inside the organ.




Fig 2. Segmentation results in axial and sagittal reformatting (blue arrow: seed point)

Conclusion

In this abstract, we present segmentation results for the prostate gland in MRI data using a recently developed method. A graph driven method has been used that is based on a spherical template. The algorithm prefers spherically- and elliptically-shaped 3D objects and has already been evaluated with glioblastoma multiforme, pituitary adenoma and cerebral aneurysm data [7]. There are several areas of future work including comparison with level-set based prostate segmentation methods such as [8], extensions for automatic segmentation of structures adjacent to the central prostate gland, such as the peripheral prostatic zone. An immediate next application for MR-guided biopsy is the generation of regions of interest towards automatic registration of preoperative to intraoperative images.



References

1. National Institutes of Health Cancer Topics: Prostate, <http://www.cancer.gov/cancertopics/types/prostate>
2. D'Amico AV, Cormack RA & Tempany CM. MRI-Guided Diagnosis and Treatment of Prostate Cancer. N Engl J Med. 344:776-777, 2001.
3. Egger J, et al. Nugget-Cut: A Segmentation Scheme for Spherically- and Elliptically-Shaped 3D Objects. In: 32nd Annual Symposium of the German Association for Pattern Recognition (DAGM), LNCS 6376, pp. 383-392, Springer, 2010.
4. Fedorov A, et al. Image Registration for Targeted MRI-guided Prostate Transperineal Prostate Biopsy. J Magn Res Imag, 2012.
5. Boykov Y & Kolmogorov V. An Experimental Comparison of Min-Cut/Max-Flow Algorithms for Energy Minimization in Vision. IEEE Transactions on Pattern Analysis and Machine Intelligence, 26(9), pp. 1124-1137, 2004.
6. Yin Y, et al. Fully automated 3D prostate central gland segmentation in MR images: a LOGISMOS based approach. Proc. SPIE 8314, 83143B, 2012.
7. Egger J, et al. Template-Cut: A Pattern-Based Segmentation Paradigm. Nature - Scientific Reports, Nature Publishing Group, 2(420), 2012.
8. Tsai A, et al. A shape-based approach to the segmentation of medical imagery using level sets. IEEE TMI, 22(2), pp.137-154, 2003.

Acknowledgements

We acknowledge the help of Drs. Fedorov, Tuncali, Fennessy and Tempany for sharing the provided data collection. This work is supported by NIH 8P41EB015898-08 and 5P01CA067165-13. Its contents are solely the responsibility of the authors and do not necessarily represent the official views of the NIH.